TCB

GRANT OF EQUIPMENT AUTHORIZATION

TCB

Certification
Issued Under the Authority of the
Federal Communications Commission
By:

Telefication B.V. Edisonstraat 12a Zevenaar, NL-6902 PK Netherlands

Date of Grant: 12/20/2019

Application Dated: 12/20/2019

Exelonix GmbH Washingtonstrasse 16/16a Dresden, 01139 Germany

Attention: Thomas Augustin

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: 2AUC4-VODEXL-01

Name of Grantee: Exelonix GmbH

Equipment Class: PCS Licensed Transmitter

Notes: USB Connector for the cellular IoT

Networks (NB-IoT/LTE-M) in a simple

wav.

Grant Notes	FCC Rule Parts	Frequency Range (MHZ)		Output Frequer <u>Watts</u> <u>Toleran</u>			Emission <u>Designator</u>
	27	699.1	- 716.0	0.251	1.0 F	M	1M11G7D
	27	699.0	- 716.0	0.269	1.0 F	М	1M11W7D
	27	699.0	- 716.0	0.148	1.0 F	M	134KF7W
	27	699.0	- 716.0	0.218	1.0 F	M	190KF7W
	27	1710.0	- 1755.0	0.245	1.0 P	M	1M24G7D
	27	1710.0	- 1755.0	0.245	1.0 F	M	1M13W7D
	27	1710.0	- 1755.0	0.188	1.0 P	M	78K7F9W
	27	1710.0	- 1755.0	0.191	1.0 P	M	196KF9W
	22H	824.0	- 849.0	0.316	1.0 F	M	1M11G7D
	22H	824.0	- 849.0	0.316	1.0 P	M	1M11W7D
	22H	824.0	- 849.0	0.169	1.0 P	M	130KF7W
	22H	824.0	- 849.0	0.199	1.0 P	M	192KF7W
	24E	1850.0	- 1910.0	0.302	1.0 F	M	1M12G7D
	24E	1850.0	- 1910.0	0.302	1.0 F	М	1M12W7D

24E	1850.0 - 1910.0	0.199	1.0 PM	132KF7W
24E	1850.0 - 1910.0	0.211	1.0 PM	192KF7W
27	777.0 - 787.0	0.269	1.0 PM	1M13G7D
27	777.0 - 787.0	0.275	1.0 PM	1M21W7D
27	777.0 - 787.0	0.146	1.0 PM	134KF7W
27	777.0 - 787.0	0.228	1.0 PM	190KF7W
27	779.5 - 784.5	0.179	0.002 PM	1M18G7D
27	779.5 - 784.5	0.173	0.002 PM	1M34W7D
27	782.0 - 782.0	0.169	0.002 PM	1M20G7D
27	782.0 - 782.0	0.168	0.002 PM	1M22W7D

C2PC: adding host.

Output power listed is conducted. This is a portable device. The SAR data in this filling is applicable to demonstrate compliance for body operating conditions and is limited to the specific configuration tested for this filling. SAR has been evaluated at 5 mm. End-users must be informed regarding RF exposure compliance. The highest reported Body SAR value is 0.87 W/kg.

